



Specification:

MODEL	MD - 30 B		MD - 30N	MD - 30M
Drilling capacity	Steel	32 mm 1-1/4"	32 mm	1-1/4"
Tapping capacity		19 mm 3/4"	19 mm	3/4"
Face mill capacity		76 mm 3"	76 mm	3"
Swing		405 mm 16"	430 mm	17"
Spindle taper	MT #3, R8, NT #30		MT #3, R8	
Spindle travel		130mm 5"	110 mm	4.3"
Quill diameter		75 mm 3"	62 mm	2-7/16"
Column diameter		115 mm 4-1/2"	95 mm	3-3/4"
Spindle nose to table		480 mm 18"	395 mm	15.5"
X axis travel		430 mm 16.9"	350 mm	13.7"
Y axis travel		190 mm 7.5"	180 mm	7"
Table size (L x W)		730 x 210 mm 28.7" x 8.3"	660 x 190 mm	26" x 7.5"
Table slot		18mm 5/8"	16 mm	5/8"
Base size (L x W)		610 x 400 mm 24" x 15.7"	560 x 340	22" x 13.4"
Spindle speed		12 Speed 50 HZ: 4P: 90 ~ 2150 12 Speed 60 HZ: 110 ~ 2580	8 P: 50 ~ 1040 8 P: 60 ~ 1250	
Motor		1-1/2 (2 HP)	3/4 (1 HP)	1 (1-1/2 HP)
Coolant motor		1/8 HP / 3 PH		
Machine size (L x W x H)		1080 x 1100 x 1100 mm 42.5" x 43.3" x 43.3"	950 x 1030 x 980 mm	37.4" x 40.5" x 38.5"
Stand size (L x W x H)		750 x 560 x 790 mm	29.5" x 22" x 31"	
Net weight		270 Kgs		180 Kgs
Measurement		27.4 CU. FT.		24 CU. FT.



 Specification:

MODEL		MD - 930	
Drilling capacity	Steel	MT 3 32 mm	1-1/4"
		MT 4 40 mm	1-1/2"
Tapping capacity		19 mm	3/4"
Swing		465 mm	18.3"
Spindle taper		MT #3, MT #4	
Spindle travel		150 mm	6"
Quill diameter		75 mm	3"
Column diameter		115 mm	4-1/2"
Spindle nose to table		460 mm	18"
X axis travel		430 mm	16.9"
Y axis travel		230 mm	9"
Table size (L x W)		730 x 210 mm	28.7" x 8.3"
Table slot		16 mm	5 / 8"
Base size (L x W)		670 x 400 mm	26.3" x 15.7"
Spindle speed		High: 245 ~ 2000 rpm Low: 65 ~ 540 rpm	
Motor		2 HP / 3 PH	
Coolant motor		1/8 HP / 3 PH	
Machine size (L x W x H)		1050 x 1100 x 1370mm	
		41.3" x 43.3" x 54"	
Stand size (L x W x H)		750 x 560 x 790mm	
		29.5" x 22" x 31"	
Net weight		287 Kgs	
Measurement		27.4 CU. FT.	